


Product Datasheet model i-3 s 9190 080

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

| | |
|--------------------------------|--|
| Product characteristics | <ul style="list-style-type: none">• fashionable, 3-component safety spectacles with innovative features• small version of standard model uvex i-3• metal-free• reliable protection provided by its perfect fit: multi-level side arm inclination allows the wearer to adjust the spectacles to suit their own face shape• soft, adjustable nose loops, soft, anti-slip sidearm pieces and metalfree hinged side arms (3-component technology) for high wearer comfort and to avoid pressure points• suitable for Oil & Gas Applications |
| Technical details | |
| Frame | Front piece/Temple |
| Material | TPU/TPE |
| Features | variable inclination, individually adjustable |
| Colour | black, grey |

| | |
|---|---|
| Manufacturer's ID code | Marking W |
| Applicable EN norm | 166 |
| Impact resistance | F (45 m/s) |
| Resistance to high speed particles at extremes of temp. | T |
| Conformity symbol | CE |
| Lens | |
| Material | PC |
| Thickness | 2,2 mm |
| Coating | uvex supravision plus |
| Colour | clear |
| UV protection | UV 400 |
| | Marking |
| Filter | 2C-1,2 (DIN EN 170) |
| Manufacturer's ID code | W |
| Optical class | 1 |
| Impact resistance | F (45 m/s) |
| Resistance to high speed particles at extremes of temperat. | T |
| Surface resistance to fine particles | K |
| Antifog | N |
| Conformity symbol | CE |
| Factory symbol |  |

Miscellaneous

Weight

30 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 170

PPE Category

Category II